TE-20-01/LED Linear bar






















Size:





TE-20-01/LED Linear bar



Features:

- 1. Minimal / minimalist lamp body appearance design meets modern industrial aesthetic standards
- 2. No glue full structure waterproof adopts new patented technology and technology
- 3. Arc cover and light guide end cover are adopted for uniform and frameless lighting effect
- 4. Square quick waterproof joint adopts patent technology of automobile piston type with nano
- 5. The luminous mask is made of 3mm imported PC material, which has good UV resistance and corrosion resistance

Parameter:

Lamp Parameter		LED parameter	
Beam Angle	120°	LED chip	Cree/OSRAM
Case material/color	Aviation grade aluminum alloy(Grey)	LED Item	CLX6E/2835
Cover material/color	Frosted PC cover	ССТ	Single color/RGB/RGBW
IP rate	IP66 structure waterproof	LED Life	50000 h
Lamp Power	12W/15W	Other Parameter	
Input Voltage	DC24V	Cable size	5 pins rubber cable(power cable 1 mm²,signal cable 0.3mm²), connector:ф16mm Aluminium alloy +ф1.5mm Gold-plated solid Pins
Pixel segment	ON/OFF/8 PIXELS		
Light Efficiency	75lm/w(white)	Cable length	150mm
Light angle	Fixing clip for option	Fixing clip	6063 Aluminium alloy
Cable location	From the bottom	Light distribution	
Control way	ON-OFF/DMX512	-/+180 -120 -90 -90 -90 -90 -90 -90 -90 -9	
Series connection quantity	10pcs		